

Boom/Stick Option (HEX) 1

Shipping Length of Unit	15.5 ft in
Shipping Height of Unit	8.4 ft in
Max Cutting Height	14.7 ft in
Max Loading Height	10.2 ft in
Max Reach Along Ground	17.1 ft in
Max Vertical Wall Digging Depth	7.8 ft in
Max Digging Depth	10.3 ft in

Dimensions

Width to Outside of Tracks	5.8 ft in
Length of Track on Ground	5.6 ft in
Ground Clearance	1.2 ft in
Height to Top of Cab	8.4 ft in
Tail Swing Radius	2.8 ft in
Counterweight Clearance	1.8 ft in

Specifications

Engine Make	Isuzu
Model	3LD2
Gross Power	32 hp
Power Measured @	2450 rpm
Displacement	91.5 cu in

Operational

Operating Weight	7760 lb
Fuel Capacity	10.5 gal
Hydraulic System Fluid Capacity	7.9 gal
Operating Voltage	12 V
Alternator Supplied Amperage	35 amps
Hydraulic Pump Flow Capacity	17.9 gal/min

Swing Mechanism

Swing Speed	8.9 rpm
-------------	---------

Undercarriage

Shoe Size	11.8 in
300 mm	
Ground Pressure	4.4 psi

Max Travel Speed	2.8 mph
------------------	---------

Buckets

Reference bucket Capacity	0.12 yd3
Minimum Bucket Capacity	0.06 yd3
Maximum Bucket Capacity	0.22 yd3