



# MARYLAND PIPE & SUPPLY CO., LLC



## PEX Brass Fittings

### SUBMITTAL AND DATA SHEET

**\*NSF & UPC Approved**      **\*Can Be Used with Pex Tubing**

**\*Manufactured to ASTM Standard F1807**

**\*Manufactured to ASTM Standard F876-877**

### SUBMITTAL INFORMATION

**\*Typical Applications:** Potable code & hot domestic water hydronic heating systems & radiant heating systems

**\*Use with:** Pex tubing in accordance with ASTM F876 & F877

**\*Material:** Forged No-Lead Brass

**\*Vibration:** Excellent resistance

**\*Complies with NSF/ANSI 61-2012**

**\*Adapter threads to ANSI B1.20.1, Adapter solder ends to ANSI B16.18. All CNC machined ends.**

**\*Pressure & Temperature:**

160 PSI @ 73°F

100 PSI @ 180°F

80 PSI @ 210°F

---

### PEX Poly Alloy Fittings

#### **Features & Benefits:**

**\*Modified Polyphenylsulfone (PPSU)**

**\*Molded from Acudel® Resin**

**\*Lead Free Compliant**

**\*Approvals: NSF 14, NSF/ANSI 61/Annex G; ASTM F2159, F877; CSA B137.5**

**\*For use in Hot and Cold Potable Water Distribution Systems**

**\*200°F Max Service Temperature**